

<http://ml.free.fr>

To get list Info mailto:fpsold-request@ml.free.fr?subject=info
Flag Configuration mailto:fpsold-request@ml.free.fr?subject=stats
List Help mailto:fpsold-request@ml.free.fr?subject=help
Statistics mailto:fpsold-request@ml.free.fr?subject=review
List of Lists mailto:fpsold-request@ml.free.fr?subject=lists
List of Members mailto:fpsold-request@ml.free.fr?subject=who
List of Commands mailto:fpsold-request@ml.free.fr?subject=commands

Command	Syntax	Description
authpwd	authpwd <cookie>	Authenticate a password change
password	password <password>	Authenticates a user with the given password.
setpassword	setpassword <newpassword>	Allows a user to set or change their password.
predigest	predigest [<list>]	Retrieves the current digest issue in whatever state it is currently in.
--	--	RFC-defined message/signature divider, ends processing of commands.
end	end	Ends processing of list server commands
info	info [<list>] info (admin only)	Retrieves the info for a list.
faq	faq [<list>] faq (admin only)	Retrieves the FAQ for a list. Members only.
setrole (ADMIN)	setrole <address> <position> (admin only)	Sets the position of a user for user tracking in 'review'
setname (ADMIN)	setname <address> <name> (admin only)	Sets the name for a user for user tracking in 'review'
which	which	Display lists to which you are subscribed
who	who [<list>]	Display membership for a list
help	help	Send user the helpfile
lists	lists	Send list of mailing lists available on this site.
commands	commands	Send list of available commands, providing a 'cheat sheet' for users. This takes into account any local plugins.
flags	flags	Send list of available flags, providing a 'cheat sheet' for users. This takes into account any local plugins.
files	files	Send list of installed list config files. Modules are not required to register a file in order to use it, so hidden config files might be present.
modules	modules	Send list of installed plugins. Plugins are not required to list themselves in this registry, so hidden plugins may be present.
review	review [<list>]	Displays current list statistics.
stats	stats [<list>] stats [<address>] (admin only)	Displays current account configuration and statistics.
tempban (ADMIN)	tempban <user> [<duration>] (admin only)	Temporarily ban a user for a specified duration
vacation	vacation [<list>] [<duration>] vacation <user> [<duration>] (admin only)	Set user on vacation for specified duration
setaddy	setaddy <address>	Reset address to same user on a sub-domain
leave	leave [<list>] [<user>] leave <user> (admin only)	Alias for unsubscribe.
join	join [<list>] [<user>] join <user> (admin only)	Alias for subscribe
add	add [<list>] [<user>] add <user> (admin only)	Alias for subscribe
remove	remove [<list>] [<user>] remove <user> (admin only)	Alias for unsubscribe.
signoff	signoff [<list>] [<user>] signoff <user> (admin only)	Alias for unsubscribe.
del	del [<list>] [<user>] del <user> (admin only)	Alias for unsubscribe.
submodes	submodes [<list>]	Show the admin specified subscription modes.

Command	Syntax	Description
submode	submode <mode> [<list>] [<user>] submode <mode> <user> (admin only)	Subscribe to a list in an admin specified mode
subscription	subscription [<list>] [<user>] subscription <user> (admin only)	Alias for subscribe
subscribe	subscribe [<list>] [<user>] subscribe <user> (admin only)	Subscribe to a list
unsubscribe	unsubscribe [<list>] [<user>] unsubscribe <user> (admin only)	Unsubscribe from a list
appunsub	appunsub <list> <address> <cookie>	Confirm unsubscription from list
appsub	appsub <list> <address> <cookie>	Confirm subscription to list.
set	set [<list>] <flag>	Sets a user variable.
unset	unset [<list>] <flag>	Unsets a user variable.
admin2 (ADMIN)	admin2 <list> (admin only)	Request administrator mode and fill out wrapper.
admin (ADMIN)	admin <list> (admin only)	Request administrator mode.
adminvfy (ADMIN)	adminvfy <list> <cookie> (admin only)	Begin administrator mode.
become (ADMIN)	become [<address>] (admin only)	Becomes another user, or cancels a become.
setfor (ADMIN)	setfor <address> <flag> (admin only)	Changes settings for another user.
unsetfor (ADMIN)	unsetfor <address> <flag> (admin only)	Changes settings for another user.
getconf (ADMIN)	getconf <file> (admin only)	Requests an admin configuration file.
putconf (ADMIN)	putconf <list> <cookie> (admin only)	Replaces an admin configuration file.
adminend (ADMIN)	adminend (admin only)	Marks end of admin mode.
get	get [<list>] <file>	Retrieve a specific file.
index	index [<list>]	List available files.